



- NOTES:
1. ALL DIMENSIONS ARE IN MILLIMETERS.
 - ② TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN, GLASS IS BEVELED UNDER THE TRANSDUCERS.
 - ③ CABLE ROUTING ADDS A MAXIMUM OF 4.0mm TO INDICATED SECTION OF SCREEN.
 - ④ 8X19 HOUSING MATES WITH CONTROLLER.
 - ⑤ REFLECTIONAL ARRAY AND ② TRANSDUCER ON THE FRONT OF THE GLASS.
 - ⑥ CABLE CLIP , MATERIAL: METAL.
 - ⑦ GLASS BOARD.
 - ⑧ CABLE , OUTER LAYER MATERIAL: PVCBG01.
 9. THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.
 10. BLACK TAPES ARE APPLIED ON THE BACK SURFACE OF THE GLASS OPPOSITE THE ARRAY PATTERNS.
 11. IT SHALL BE AVOIDED FOR ② TO UNDERGO COMPRESSION,IMPACT, CRASH AND BREAK UP.

External Dimensions	382x312x6
Display Area	346x278
Active Area	340x272
Glass Thickness	6
Anti-Glare	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
DustPro	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
WaterPro	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
Anti-Vandal	Y <input checked="" type="checkbox"/> N <input type="checkbox"/>

CONNECTION CHART

PIN	SIGNAL	INSULATION COLOR OVERALL SHIELD
1	GND	
2	KEY	
3	Y-in2	BLUE
4	Y-out	BLUE
5	Y-in1	BLACK
6	GND	YELLOW
7	GND	
8	GND	GREEN
9	X-in2	WHITE
10	X-out	RED
11	X-in1	RED
12	KEY	