



- NOTES:
1. ALL DIMENSIONS ARE IN MILLIMETERS.
  2. TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN, GLASS IS BEVELED UNDER THE TRANSDUCERS.
  3. CABLE ROUTING ADDS A MAXIMUM OF 4.0mm TO INDICATED SECTION OF SCREEN.
  4. 8X19 HOUSING MATES WITH CONTROLLER.
  5. REFLECTIONAL ARRAY AND 2 TRANSDUCER ON THE FRONT OF THE GLASS.
  6. CABLE CLIP , MATERIAL: METAL.
  7. GLASS BOARD.
  8. CABLE , OUTER LAYER MATERIAL: PVCBG01.
  9. THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.
  10. IT SHALL BE AVOIDED FOR 2 TO UNDERGO COMPRESSION,IMPACT, CRASH AND BREAK UP.

External Dimensions	520x343
Viewable Area	478x300
Glass Thickness	6
Anti-Glare	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
DustPro	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
WaterPro	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
Anti-Vandal	Y <input checked="" type="checkbox"/> N <input type="checkbox"/>

CONNECTION CHART		
PIN	SIGNAL	INSUTLATION COLOR OVERALL SHIELD
1	GND	
2	NC	
3	Y-in2	BLUE
4	Y-out1	BLUE
5	Y-in1	BLACK
6	Y-out2	YELLOW
7	GND	
8	X-out1	GREEN
9	X-in2	WHITE
10	X-out2	RED
11	X-in1	RED
12	NC	